



REV	DESCRIPTION	ECN NO.	DATE
△			

接线点	
P1	P2
1 红色	1
2 白色	2
3 绿色	3
4 黑色	5
5 蓝色	6
6 黄色	7
7 地线	8
8 地线	8
9 紫色	9
10 橙色	10
Shell 地线	Shell

9	纸箱	外箱:L600*W:360*H:250MM A=A	T603625	1	PCS
8	胶袋	透明PE胶袋:250*250*0.04MM	T250250	1	PCS
7	胶袋	透明PE胶袋:150*160*0.03MM	T150160	1	PCS
6	扎带	扎带:110MM 蓝色		2	PCS
5	外模料	45P 蓝色PVC胶料	PVC-WU-45P	14	G
4	内模料	内模料 LD-PE	LD-PE	3.6	G
3	插头	MICRO B型 三件式 黑色胶芯 端子镀金30 U"		1	Set
2	插头	USB3.0 A/M 蓝色胶芯 端子镀金30 U"	C-USBAM3.0-02	1	Set
1	线材	UL20276 (1P*28#+D+AL+M)2C+1P*28#+2C*24#+F+AL+B LM16*6 OD:5.5mm 蓝色外被	B-USB3.0-BU-5.5	1.5	M
NO 序号	P/NAME 名称	DESCRIPTION 规格说明	COMPANY MATERIALS ISSUE 公司料号	Q'TY 数量	UNIT 单位

GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE:	NUMBER:
UNIT	MM	MATERIAL:	HRC:
.X	±0.38	DRAWN BY DATE	
.XX	±0.25	: WZH	
.XXX	±0.13	CHECKED BY DATE	
ANGULAR ±3°		:	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			

东莞市鸿威精密电子有限公司 Dongguan HongWei Electronic CO.,LTD	
NAME: USB AM TO MICRO BM 3.0	
DWG NO. HW-CB-USB-020-002	REV: A/0
THIRD ANGLE PROJECTION	DATE: 2013.11.28